

Cisco 2-Port, 5-Port, 8-Port, and 10-Port Gigabit Ethernet Shared Port Adapters

The Cisco® I-Flex approach combines shared port adapters (SPAs) and SPA interface processors (SIPs), providing an extensible design that enables service prioritization for data, voice, and video services. Enterprise and service provider customers can take advantage of improved slot economics resulting from modular port adapters that are interchangeable across Cisco routing platforms. The Cisco I-Flex design maximizes connectivity options and offers superior service intelligence through programmable interface processors that deliver line-rate performance. Cisco I-Flex enhances speed-to-service revenue and provides a rich set of quality-of-service (QoS) features for premium service delivery while effectively reducing the overall cost of ownership. This data sheet contains the specifications for the Cisco 2-Port, 5-Port, 8-Port, and 10-Port Gigabit Ethernet SPAs (Figure 1).

Figure 1. Cisco 5-Port and 10-Port Gigabit Ethernet SPAs



Product Overview

The Cisco 2-port, 5-port, 8-port, and 10-port Gigabit Ethernet SPAs are available on high-end Cisco routing platforms offering the benefits of network scalability with lower initial costs and easy upgrades. The Cisco SPA/SIP portfolio continues the company's focus on investment protection along with consistent feature support, broad interface availability, and the latest technology. The Cisco SPA/SIP portfolio allows deployment of different interfaces (packet over SONET/SDH [POS], ATM, Ethernet, etc.) on the same interface processor.

Gigabit Ethernet interfaces are commonly used for interconnecting routers or other devices within a central office or data center or in a metropolitan-area network (MAN). Cisco offers an extensive variety of 1000BASE-X Gigabit Ethernet SPAs to meet customers' needs for various applications. With Cisco Gigabit Ethernet SPAs, users can mix-and-match SPA ports with other types of interfaces in the same slot. Each SPA provides standards-based Gigabit Ethernet implementation for compatibility and interoperability.

Applications

The Cisco Gigabit Ethernet SPAs can be used in multiple applications, including:

- Inter- and intra-point of presence (POP) aggregation
- Metro Ethernet
- Internet peering

Key Features and Benefits

The Cisco SPA/SIP portfolio offers many advantages, including:

- Highly modular, flexible, intelligent interface processors
 - Superior flexibility, providing mix-and-match capability of interface types on the same interface processor for consistent services, independent of access technology
 - Pioneering programmable interface processors that provide flexibility for the service diversity required in next-generation networks
 - Innovative design that provides intelligent delivery of services without compromising on performance
- Increased speed-to-service revenue
 - The scalable, programmable Cisco architecture extended to 10 Gbps dramatically improves customer density, increasing potential revenue per platform.
 - Interface breadth (copper, channelized, POS, ATM, and Ethernet) on a modular interface processor allows service providers to roll out new services more quickly, helping ensure that all customers large and small receive consistent, secure, and guaranteed services.
 - High-density Small Form-Factor Pluggable (SFP) interfaces are featured for high-port-count applications with reach flexibility. Future optical technology improvements can be adopted using existing SPAs.
- Dramatically improved return on your routing investment
 - Improved slot economics and increased density reduce capital expenditures (CapEx).
 - The ability to easily add new interfaces as they are needed helps enable a "pay-as-you-grow" business model.
 - SPAs are shared across multiple platforms, and can be easily moved from one to another, providing consistent feature support, accelerated product delivery, and a significant reduction in operating expenses (OpEx) through common sparing as service needs change.

Product Specifications

Tables 1 and 2 provide product and optical specifications of the Cisco Gigabit Ethernet SPAs.

Table 1. Product Specifications

Features	Descriptions
Product compatibility	<ul style="list-style-type: none"> • Cisco Catalyst 6500 Series Switches (2-port, 5-port, and 10-port Gigabit Ethernet [GE] SPAs) • Cisco 7600 Series Router (2-port, 5-port, and 10-port GE SPAs) • Cisco 12000 Series Router (5-port and 10-port GE SPAs) • Cisco XR 12000 Series Router (5-port and 10-port GE SPAs) • Cisco CRS Carrier Routing System (8-port GE SPA)
Port density per SPA	2-port, 5-port, 8-port, and 10-port Gigabit Ethernet

Physical interface	Short wavelength (SX), long reach/long haul (LX/LH), and extended distance (ZX) SFP, SFP-GE-T
LED Indicators	<ul style="list-style-type: none"> • SPA status: Bicolor green and amber LEDs encode the SPA status as follows: <ul style="list-style-type: none"> ◦ LED off: SPA is powered off ◦ LED amber: SPA is powered on and initializing ◦ LED green: SPA is powered on and operational • In addition to the status LED, the SPAs also have a bicolor, surface-mount, right-angle LED dedicated to each port to indicate port status. The green and amber LEDs encode the port status as follows: <ul style="list-style-type: none"> ◦ LED off: Port is not enabled by software ◦ LED: Port is enabled by software, but there is a problem with the Ethernet link ◦ LED green: Port is enabled by software, and there is a valid Ethernet link
Features and Functions	<ul style="list-style-type: none"> • Auto-negotiation • Full-duplex operation • 802.1Q VLAN termination • Jumbo frames support (9188 bytes) • Support for command-line interface (CLI)-controlled online insertion and removal (OIR) • 802.3x flow control • Up to 4000 VLANs per SPA • Up to 5000 MAC accounting entries per SPA (source MAC accounting on the ingress and destination MAC accounting on the egress) • Up to 2000 MAC address entries for destination MAC address filtering per SPA, and up to 1000 MAC address filtering entries per port • Per-port byte and packet counters for policy drops; oversubscription drops; cyclic-redundancy-check (CRC) error drops; packet sizes; and unicast, multicast, and broadcast packets • Per-VLAN byte and packet counters for policy drops; oversubscription drops; and unicast, multicast, and broadcast packets • Per-port byte counters for good bytes and dropped bytes • Other software features supported: <ul style="list-style-type: none"> • Ethernet over Multiprotocol Label Switching (EoMPLS) • QoS • Hot Standby Router Protocol (HSRP) • Virtual Router Redundancy Protocol (VRRP)
Network Management	<ul style="list-style-type: none"> • Network management using: <ul style="list-style-type: none"> ◦ Host-system CLI ◦ Simple Network Management Protocol (SNMP) • Inventory- and asset management-related MIBs: <ul style="list-style-type: none"> ◦ Entity-MIB (RFC 2737) ◦ Cisco-entity-asset-MIB • Fault management: <ul style="list-style-type: none"> ◦ Cisco-entity-field-replaceable unit (FRU)-control-MIB ◦ Cisco-entity-alarm-MIB ◦ Cisco-entity-sensor-MIB • Physical interface management: <ul style="list-style-type: none"> ◦ IF-MIB ◦ Etherlike-MIB (RFC 2665) • Other MIBs: <ul style="list-style-type: none"> ◦ Remote Monitoring (RMON)-MIB (RFC 1757) ◦ Cisco-class-based-QoS-MIB ◦ MPLS-related MIBs ◦ Ethernet MIB/RMON
Reliability and Availability	<ul style="list-style-type: none"> • OIR of the SPA within the SIP and the optics within the SPA • Field-replaceable SFP optical modules

Physical Specifications	<ul style="list-style-type: none"> • 2-port, 5-port, and 8-port GE SPAs: • Weight: 0.75 lb (0.34 kg) • Height: 0.8 in. (2.03 cm) (single height) • Width: 6.75 in. (17.15 cm) • Depth: 7.28 in. (18.49 cm) • 10-port GE SPA: • Weight: 1.5 lb (0.68 kg) • Height: 1.4 in. (3.55 cm) (double height) • Width: 6.75 in. (17.15 cm) • Depth: 7.28 in. (18.49 cm)
Power	<ul style="list-style-type: none"> • 2-port GE SPA: 12.5W • 5-port GE SPA: 18.1W • 8-port GE SPA: 20W • 10-port GE SPA: 25W
Environmental Specifications	<ul style="list-style-type: none"> • Storage temperature: –38 to 150°F (–40 to 70°C) • Operating temperature, nominal: 32 to 104°F (0 to 40°C) • Operating temperature, short term: 32 to 131°F (0 to 55°C) • Storage relative humidity: 5 to 95% relative humidity • Operating humidity, nominal: 5 to 85% relative humidity • Operating humidity, short term: 5 to 90% relative humidity • Operating altitude: –60 to 4000 meters
Compliance and Agency Approvals	<p>Safety</p> <ul style="list-style-type: none"> • UL 60950-1 • CSA C22 No. 60950-1 • EN 60950-1 • IEC 60950-1 • AS/NZS 60950 • EN 60825-1 • EN 60825-2 • 21 CRF 1040 <p>EMC</p> <ul style="list-style-type: none"> • CFR 47 • FCC Part 15-Class A • ICES 003-Class A • CISPR 22 Class A • EN 55022 Class A • EN 300386 Class A • AS/NZS Class A • VCCI-Class B • EN 50082-1 • EN 55024 • IEC/EN61000-4-2 Electrostatic Discharge Immunity (8-kV contact, 15-kV air) • IEC/EN61000-4-3 Radiated Immunity (10 V/m) • IEC/EN61000-4-4 Electrical Fast Transient Immunity (2-kV power, 1-kV signal) • IEC/EN61000-4-5 Surge AC Port (4-kV CM, 2-kV DM) • IEC/EN61000-4-5 Surge Signal Port (1-kV indoor, 2-kV outdoor) • IEC/EN61000-4-5 Surge DC Port (1 kV) • IEC/EN61000-4-6 Immunity to Conducted Disturbances (10 Vrms) • IEC/EN61000-4-8 Power Frequency Magnetic Field Immunity (30 A/m) • IEC/EN61000-4-11 Voltage Dips, Short Interruptions, and Voltage Variations <p>Telecom</p> <ul style="list-style-type: none"> • IEEE 802.3z • Industry Standards <p>The Cisco Gigabit Ethernet SPAs are designed to meet the following requirements (some qualifications are currently in progress):</p> <ul style="list-style-type: none"> • SR-3580-Network Equipment Building Standards (NEBS): criteria levels (Level 3 compliant) • GR-63-CORE-NEBS: Physical protection • GR-1089-CORE-NEBS EMC and safety

Table 2. Optical Specifications: Modular

Gigabit Ethernet SFP Optics	Maximum Distance
Short Wavelength (SX) SFP Optics	1804 ft (550 m)
Long Wavelength/Long Haul (LX/LH) SFP Optics	6.2 mi (10 km)
Extended Distance (ZX) SFP Optics	43.5 mi (70 km)

Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#) or refer to Table 3.

Table 3. Ordering Information

Product Name	Part Number
Cisco 2-Port Gigabit Ethernet Shared Port Adapter	SPA-2X1GE
Cisco 2-Port Gigabit Ethernet Shared Port Adapter, Spare	SPA-2X1GE=
Cisco 5-Port Gigabit Ethernet Shared Port Adapter	SPA-5X1GE
Cisco 5-Port Gigabit Ethernet Shared Port Adapter, Spare	SPA-5X1GE=
Cisco 8-Port Gigabit Ethernet Shared Port Adapter	SPA-8X1GE
Cisco 8-Port Gigabit Ethernet Shared Port Adapter, Spare	SPA-8X1GE=
Cisco 10-Port Gigabit Ethernet Shared Port Adapter	SPA-10X1GE
Cisco 10-Port Gigabit Ethernet Shared Port Adapter, Spare	SPA-10X1GE=
Cisco Shared Port Adapter Blank Cover	SPA-BLANK
Cisco Shared Port Adapter Blank Cover, Spare	SPA-BLANK=
Cisco Extended Temperature SX SFP	SFP-GE-S
Cisco Extended Temperature SX SFP, Spare	SFP-GE-S=
Cisco Extended Temperature LX/LH SFP	SFP-GE-L
Cisco Extended Temperature LX/LH SFP, Spare	SFP-GE-L=
Cisco Extended Temperature ZX SFP	SFP-GE-Z
Cisco Extended Temperature ZX SFP, Spare	SFP-GE-Z=
1000BASE-T SFP	SFP-GE-T
1000BASE-T SFP, Spare	SFP-GE-T=

Service and Support

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, refer to [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

For More Information

For more information about the Cisco SPA/SIP portfolio, visit <http://www.cisco.com/go/spa> or contact your local Cisco account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)

Printed in USA

C78-439909-00 02/10